

PNEUMATIC NAILING SYSTEM

AS SPECIFIED BY JUNCKERS
FOR THEIR SPORTS FLOOR SYSTEMS

New



Nail With Complete Confidence

- **Flexi-J nail** designed to retain its strength and yet flex in sympathy with the floor
- **Specified for Modular DIN, UnoBat 50 and single batten sports and dance floors**
- **Flexi-J nails** are identified by 'J' mark on small head
- Made from special heat-treated steel, phosphate coated
- Annular ring shank for added holding power
- Short pointed to minimize wood splitting
- 45mm and 50mm long x 2.2mm gauge
- Galvanized Standard floor nails without 'J' mark or heat treatment, ideal for commercial and domestic 22mm solid hardwood floors
- 200 nails per plastic coil. The plastic sheet collation passes through the tool and remains intact as each nail is fired

Max M-K Modified flooring Pneumatic Nailer

- Tool designed for accurate nail placement at a 45 degree angle.
- **The tool action will not further cramp the boards, unlike mallet driven tools, therefore, intermediate expansion allowances can be visually pre-determined before nailing and PVC spacers can be removed easily**
- Effortless operation from a standing or kneeling position.
- Fitted with a countersink adjuster Operation pressure - constant 7 bar (112psi).
- Air consumption—1 litre per shot at 112psi. Supplied in metal case

Maestri - Kear 2002 Oil free 2 hp Compressor

- Automatic, ideal for on site use
- Will deliver constant 8 bar (120 psi)
130 lts of free air @ 7bar (112psi)=130 nails/minute
- Fitted with pressure gauge & filter
- 110v or 240v available Weight - 18.5kg
Supplied in strong ply carry case
- 2 x 10 metres of airline with quick release couplings included

WE ARE
THE

S
T
R
O
N
G
E
S
T

LINK



Industrial (145psi)

Maestri-Kear (UK) Ltd

Winterpit Lane, Mannings Heath Horsham,
West Sussex. RH13 6LZ

Tel: (01403) 275757 Fax: (01403) 271270

Email: sales@maestri-kear.co.uk